# **Technical Data Sheet**



# **Bohler X-Press Rule**

#### Description

The patented back-design of this cutting rule makes way for the predefined compensation area for the cutting rule to self-level under pressure. This allows the cutting tip to be under less strain and remain sharper for a longer period of time. This means substantially longer tooling life. This rule is especially suitable for large volume jobs where highest quality is needed.



## **Physical Properties**

· ·	
Body Hardness	~340 HV (35 HRC)
Tip Hardness	~660 HV (58 HRC)
Bevel Angle	53° / 42°
Point Thickness	2, 3
Height	23.8mm (0.937")
Bevel Finish	S, P

## **Availability & Ordering Information**

Steel rule is available in four bevel profiles:

- CF (Center Face, Single Bevel)
- SF (Side Face, Single Bevel)
- CFDB (Center Face, Double Bevel)
- SFDB (Side Face, Double Bevel)

Bohler X-Press is available in two bevel finishes:

- Shaved
- Polished

Steel rule in 30", 36", and meter lengths can be purchased by the piece. Clockwise, anti-clockwise, and dispenser coils are sold in full coils only.

•

The user shall determine the suitability of this product for their application and assumes all risks and liabilities associated with the use of this product. The exclusive remedy for all proven claims is replacement of our materials only and in no events shall Freeman Mfg. & Supply Co. be liable for special, incidental, or consequential claims.

READ SAFETY DATA SHEETS AND PRODUCT LABELS BEFORE USING PRODUCT

