

Bohler X-Press Pure Rule

Description

The slimlined back execution of this cutting rule combined with the patented micro-serration allows for make-ready without patching. This rule provides best results with small to medium size production runs of corrugated and solid board.



Physical Properties

Body Hardness	~340 HV (35 HRC)
Tip Hardness	~660 HV (58 HRC)
Bevel Angle	53° / 42°
Point Thickness	2, 3
Height	23.8mm (0.937")
Bevel Finish	S, P

Availability & Ordering Information

Steel rule is available in four bevel profiles:

- CF (Center Face, Single Bevel)
- SF (Side Face, Single Bevel)
- CFDB (Center Face, Double Bevel)
- SFDB (Side Face, Double Bevel)

Bohler X-Press Pure is available in three bevel finishes:

- Shaved
- Polished

Steel rule in 30", 36", and meter lengths can be purchased by the piece. Clockwise, anti-clockwise, and dispenser coils are sold in full coils only.

The user shall determine the suitability of this product for their application and assumes all risks and liabilities associated with the use of this product. The exclusive remedy for all proven claims is replacement of our materials only and in no events shall Freeman Mfg. & Supply Co. be liable for special, incidental, or consequential claims.

READ SAFETY DATA SHEETS AND PRODUCT LABELS BEFORE USING PRODUCT