



Helmold Helmex Cutting Rule

Description

Helmold® Helmex is a specially formulated steel to produce an extremely durable cutting edge and enough ductility to create sharp bends.



Physical Properties

Body Hardness	45 HRC
Bendability	.016-R/2PT
Point Thickness	1.5, 2, 3, 4
Height	0.375" - 2.000"
Bevel Finish	Shaved, Buffed, Ground

Availability & Ordering Information

Steel rule is available in six bevel profiles:

- CFB (Center Face Bevel)
- CFLB (Center Face, Long Bevel)
- FB (Flush Bevel)
- MBB (Minimum Back Bevel)
- SFB (Side Face Bevel)
- SFLB (Side Face, Long Bevel)

Helmold Helmex is available in three bevel finishes:

- Shaved
- Buffed
- Ground

Steel rule in 30", 36", and meter lengths can be purchased by the piece. Clockwise, anti-clockwise, and dispenser coils are sold in full coils only.

The user shall determine the suitability of this product for their application and assumes all risks and liabilities associated with the use of this product. The exclusive remedy for all proven claims is replacement of our materials only and in no events shall Freeman Mfg. & Supply Co. be liable for special, incidental, or consequential claims.

READ SAFETY DATA SHEETS AND PRODUCT LABELS BEFORE USING PRODUCT

