



Helmold Perforating Rule

Description

Helmold® Perforating Rule is available in virtually any combination of teeth and spaces, controlled depths, tempers, bevels, heights, cut lengths or coils. For wider perforation spaces than those indicated here, see the combination cut and crease rule section.



Perforating Rule up to 1.000"

Point	Hardness	Min. Space	Max. Space	Min. Tooth	Min. Height	Max. Height	Std Depth
1.5	65	0.016	1.000	0.028	0.500	1.500	0.125
2	50	0.016	1.000	0.028	0.500	0.937	0.125
2	65	0.020	1.000	0.028	0.500	2.000	0.125
2	70	0.024	1.000	0.028	0.500	0.970	0.125
3	50	0.031	1.000	0.031	0.500	0.937	0.188
3	65	0.031	1.000	0.062	0.500	2.000	0.188
3	70	0.039	1.000	0.062	0.500	0.937	0.188
4	65	0.062	1.000	0.062	0.500	2.000	0.188

Availability & Ordering Information

Steel rule is available in six bevel profiles:

- CFB (Center Face Bevel)
- CFLB (Center Face, Long Bevel)
- FB (Flush Bevel)
- MBB (Minimum Back Bevel)
- SFB (Side Face Bevel)
- SFLB (Side Face, Long Bevel)

Steel rule in 30", 36", and meter lengths can be purchased by the piece. Clockwise, anti-clockwise, and dispenser coils are sold in full coils only.

The user shall determine the suitability of this product for their application and assumes all risks and liabilities associated with the use of this product. The exclusive remedy for all proven claims is replacement of our materials only and in no events shall Freeman Mfg. & Supply Co. be liable for special, incidental, or consequential claims.

READ SAFETY DATA SHEETS AND PRODUCT LABELS BEFORE USING PRODUCT

