



PRODUCT TECHNICAL DATA SHEET

SW066 Spray Adhesive

Distributed by
Freeman Manufacturing & Supply Co.
www.freemansupply.com (800) 321-8511



DESCRIPTION: A high-performance product perfect for use in the art studio, graphic arts or screenprinting shop, or the sign shop. No. 66 is a non-wrinkling, repositionable, water-resistant, quick or long tack adhesive that provides either a temporary or permanent bond.

USES: This spray can be used to bond many materials including: metal, cardboard, foam rubber, plastic films, glass, wood, paper and cloth. Ideal for quick layouts, paste-ups, labeling and display assembly.

SPECS:	Can Size: 16 oz.
	Net Weight: 11 oz.
	Shipping Weight: 11 lbs.
	Packaged: 12 cans per case
	UPC Number: 0 41911 00066 6

PHYSICAL CHARACTERISTICS:	Color: Tan, semi-translucent
	Fragrance: Solvent
	Shelf Life: 1 Year +

REGULATORY:	Ozone Depleting Compounds: None
	Recyclable Packaging: Yes
	VOC Compliant CARB/OTC: No
	CPSC Flame Extension: Required to be labeled as extremely flammable per 16 CFR 1500
	24 HOUR MEDICAL EMERGENCY: 1-866-836-8855



- PRODUCT FEATURES:**
- Permanent or temporary bond
 - Non-wrinkling
 - Quick tack
 - Water resistant

AFTER USE: to clear valve of adhesive - hold can bottom up and spray a small amount. Spray tips may be cleaned with turpentine.

Manufactured by:
SPRAYWAY, INC.
1005 Westgate Drive • Addison, IL 60101
800-332-9000 • Fax: 630-543-7797 • www.spraywayinc.com